

## TrackiNG-1

Portable Reader



© DATAMARS 2018

### Highlights

The TrackiNG-1 is a portable livestock reader with a “state of the art” user interface. Extremely light and easy to handle, this device has been designed to reliably scan your animals with best-in-class reading performances. It reads all ISO HDX and FDX-B transponders in accordance with ISO Standard 11784/5.

The TrackiNG-1 has an internal memory to store 4'000 ID codes, continuous reading, tag counter features and a long-lasting rechargeable battery. The included companion software will allow you to download the recorded data quickly and easily. Optional Bluetooth allows for wireless connectivity with Bluetooth enabled devices such as weigh scales, printers, computers and most mobile devices.

### Technical Specifications

|  |  |
|--|--|
| Product Name                                   | TrackiNG-1                                     |
| Size and Weight                                | 223 x 108 x 41 mm, 290 g                       |
| Power Supply                                   | Rechargeable battery (Lithium polymer 2500mAh) |
| Interface                                      | USB<br>Bluetooth (optional)                    |
| Transmission Frequency                         | 134.2 kHz                                      |
| Memory   | 4'000 IDs                                      |
| IP rate  | IP67   |
| Operating Temperature                          | -10°C to + 55°C, 85% RH non condensing         |
| Charging Temperature                           | +5°C to + 40°C, 85% RH non condensing          |
| Long-Term Storage Temperature                  | -20°C to + 45°C, 85% RH non condensing         |
| Typical Reading Distance<br>(depending on tag) | 33 cm HDX<br>30 cm FDX-B                       |
| Certifications                                 | EN 60950 - 1:2006 CE ACMA<br>FCC               |